



Yumizen C600

Technical Specifications

Throughput: 400 tests/hr (Photometric), 320 tests/hr (ISE)
600 tests/hr (photometric + ISE)

Principles: Colorimetry, Turbidimetry, Potentiometry

ISE Module (optional)
Sample Type: Serum, Plasma or Urine
Sample Volume: Na⁺, K⁺, Cl⁻, Li⁺ (optional)
Serum: 100 µL, Urine: 200 µL

Sample Handling

Sample Position: 126 (up-to 9 seg. – 14 positions/seg.)
320 tests/hr (ISE)

Barcode Reader: Yes

Barcode Positions: 81

Tube Size: 12 mm to 16 mm (height up to 100 mm)

Container Type : Vacutainer, 2ml cup, 500µL Pediatric Cup,
Test tubes, etc.

Type of Syringe: Ceramic piston pump with low maintenance

Sample Volume: From 2 µL to 40 µL

Predilution Ratio: From 1:2 to 1:200

Level & vertical collision Detector: Yes

Clot Detector: Yes

Optical System

Light Source: LEDs

Photometric Range: -0.2 A to 3.5 A

Wavelengths: 340, 405, 505, 535, 560, 600, 635, 670 nm

Filters Bandwidth: ± 2 nm

Internal Resolution: 0.0001

Photo Detector: Main Photodiode + reference photodiode

Measurement Precision: CV <1% to 0.1 A / CV <0.1% to 2 A

Electrical Requirements

Mains Voltage: 115 V to 230 V

Mains Frequency: 50 Hz or 60 Hz

Electric Power: 500 VA

Physical Information

Dimensions (W/D/H): 1200 mm x 720 mm x 1258 mm

Weight: 210 Kg

Directives and Standards Compliance

EC Directive: 98/79/EC IVD



HORIBA India Private Limited

246, Okhla Industrial Estate Phase III, New Delhi - 110020, India
Tel : +91 (11) 4646 5000 / 46695001 | Fax : +91 (11) 4646 5020 / 4669 5010, <https://www.horiba.com> | E-mail : service.hin@horiba.com



HORIBA



Smart Automation
Elevate Lab Efficiency

Yumizen C600

HORIBA

Explore the future

HORIBA

◀ Smart Technology for Accurate and Reliable Testing ▶



COUNT ON US...